Product Information Sheet

ing

control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	ELEGATED REGUI	LATION (EU) 2019/20	015 with regard to energ	gy labelling of light		
Supplier's name or trade mark: LED EVOLUTION						
Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT						
Model identifie	r: 206063					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		N/A				
(or other electric interface)						
Mains or non-mains:		MLS	Connected light source (CLS):	No		
Colour-tuneable	Colour-tuneable light source:		Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		3	Energy efficiency class	G		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		136 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 400		
On-mode power (P _{on}), expressed in W		3,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	90	Spectral power dis-	See image		
sions without	Width	90	tribution in the	in last page		
separate con- trol gear, light-	Depth	20	range 250 nm to 800 nm, at full-load			

parts and non-						
lighting con-						
trol parts, if						
any (millime-						
tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	15			
		Chromaticity coordi-	0,380			
		nates (x and y)	0,038			
Parameters for LED and OLED light sources:						
R9 colour rendering index va	lue 13	Survival factor	0,95			
the lumen maintenance factor	or 0,80					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency	3			
		in McAdam ellipses				
Claims that an LED light sou	rce -(b)	If yes then replace-	-			
replaces a fluorescent lig	ght	ment claim (W)				
source without integrated by	oal-					
last of a particular wattage.						
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-': not applicable; (b)'-': not applicable;

