Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: TECHTOUCH

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

Model identifier: 2500022

Type of light source:

| Lighting technology used: | LED | Non-directional or directional: | NDLS | | |
|-------------------------------|------|---------------------------------|------|--|--|
| Light source cap-type | N/A | | | | |
| (or other electric interface) | | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable light source: | No | Envelope: | - | | |
| High luminance light source: | No | | | | |
| Anti-glare shield: | No | Dimmable: | No | | |
| Product parameters | | | | | |

| | Floudet para | licters | | | |
|-----------------------------------|---|--|--|--|--|
| | Value | Parameter | Value | | |
| General product parameters: | | | | | |
| 00 h), rounded | 10 | Energy efficiency class | F | | |
| ers to the flux in in a wide cone | 1 000 in Sphere (360°) | Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set | 4 000 | | |
| ver (P _{on}), ex- | 10,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | | |
| expressed in W | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 | | |
| Height | 1 000 | Spectral power dis- | See image | | |
| Width Depth | 8 | tribution in the range 250 nm to 800 nm, at full-load | in last page | | |
| | andby power expressed in W the second dec- Height Width | ValueGeneral product pnption in on- 00 h), rounded st integer10aflux (фuse), in- ers to the flux in , in a wide cone rrow cone (90°)1 000 in Sphere (360°)ver (Pon), ex- expressed in W the second dec-10,0Height1 000Width8 | ValueParameterGeneral product parameters:nption in on- 00 h), rounded st integer10Energy efficiency classaflux (фuse), in- ers to the flux in in a wide cone rrow cone (90°)1 000 in Sphere (360°)Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be setver (Pon), ex- expressed in W the second dec-10,0Standby power (Psb), expressed in W the second dec-Height1 000Spectral power dis- tribution in the range 250 nm to 800 | | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | |
|--|------|------------------------------|-------|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | |
| | | Chromaticity coordi- | 0,380 | | |
| | | nates (x and y) | 0,380 | | |
| Parameters for LED and OLED light sources: | | | | | |
| R9 colour rendering index value | 3 | Survival factor | 0,95 | | |
| the lumen maintenance factor | 0,80 | | | | |
| (a) | | | | | |

(a)'-' : not applicable;

(b)'-' : not applicable;

Spectrum

