Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	LUXRAM

Supplier's address:	INTERLUSA	, Estr. interior da o	circunvalação 124	77, 4100-178 Porto, PT
---------------------	-----------	-----------------------	-------------------	------------------------

NAI - I	• .1 • • •	702242052
INIUGEI	identitier:	703213053

T	- 6	10 - 1- 1		
IVna	α T	IIσnt	source:	,
IVDC	vı	HEILL	Jourte.	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
<u> </u>			

Product parameters

		1 Todact parar		
Parameter		Value	Parameter	Value
		General product p	arameters:	
<u> </u>	nption in on- 00 h), rounded st integer	5	Energy efficiency class	G
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	280 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1 800
On-mode pow pressed in W	ver (P _{on}), ex-	5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	143	Spectral power dis-	See image
sions without	Width	64	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	64	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	27		
		Chromaticity coordinates (x and y)	0,380 0,380		
Parameters for LED and OLED I	Parameters for LED and OLED light sources:				
R9 colour rendering index value	3	Survival factor	0,95		
the lumen maintenance factor	0,80				
Parameters for LED and OLED I	mains light sources:				
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	3		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	t	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)'-': not applicable; (b)'-': not applicable;

Spectrum

