## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: LUXRAM

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

## Model identifier: 751276241

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	E27				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					

Parameter		Value	Parameter	Value		
General product parameters:						
	nption in on- 00 h), rounded st integer	18	Energy efficiency class	G		
dicating if it refeating a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	1 521 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	6 400		
On-mode pov pressed in W	ver (P <sub>on</sub> ), ex-	18,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
(P <sub>net</sub> ) for CLS,	tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	120	Spectral power dis-	See image		
sions without separate con- trol gear, light- ing control	Width Depth	65 65	tribution in the range 250 nm to 800 nm, at full-load	in last page		
				Dage 1 /		

parts and non- lighting con- trol parts, if any (millime- tre)							
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	100				
		Chromaticity coordi- nates (x and y)	0,380 0,380				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	3	Survival factor	0,95				
the lumen maintenance factor	0,80						
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	3				
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-				
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4				

(a)<sub>'-'</sub> : not applicable;

(b)'\_-' : not applicable;

