Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	LUXRAM

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

Model identifier: 7	762311123
---------------------	-----------

T۱	/pe	of	lig	ht	SO	urc	e:
•)	, PC	0.	יסיי		30	u	•

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Froduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
0,	mption in on- 00 h), rounded st integer	4	Energy efficiency class	F	
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone errow cone (90º)	350 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode power (P _{on}), expressed in W		4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimensions without	Height Width	82 45	Spectral power distribution in the	See image in last page	
separate con- trol gear, light- ing control	Depth	45	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime-					
tre)					
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	32		
		Chromaticity coordi-	0,380		
		nates (x and y)	0,380		
Parameters for LED and OLED li	ght sources:				
R9 colour rendering index value	3	Survival factor	0,95		
the lumen maintenance factor	0,80				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	3		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)'-': not applicable; (b)'-': not applicable;

Spectrum

