## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

Model identifier: 763431143

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

LED	Non-directional or directional:	NDLS
E14		
MLS	Connected light source (CLS):	No
No	Envelope:	-
No		
No	Dimmable:	No
	E14  MLS  No  No	MLS Connected light source (CLS):  No Envelope:  No

## **Product parameters**

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consummode (kWh/10) up to the neares	00 h), rounded	4	Energy efficiency class	F	
Useful luminous dicating if it refe a sphere (360°), (120°) or in a na	ers to the flux in , in a wide cone	400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked st (P <sub>net</sub> ) for CLS, e and rounded to imal	•	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	100	Spectral power dis-	See image	
sions without	Width	35	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	35	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	35		
		Chromaticity coordinates (x and y)	0,380 0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	3	Survival factor	0,95		
the lumen maintenance factor	0,80				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	2		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)'-': not applicable; (b)'-': not applicable;

## Spectrum

