Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUXRAM

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

Model identifier: 764181042

Type of light source:

Product parameters						
Anti-glare shield:	No	Dimmable:	No			
High luminance light source:	No					
Colour-tuneable light source:	No	Envelope:	-			
Mains or non-mains:	MLS	Connected light source (CLS):	No			
(or other electric interface)						
Light source cap-type	G13					
Lighting technology used:	LED	Non-directional or directional:	NDLS			

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	mption in on- 000 h), rounded est integer	14	Energy efficiency class	F		
indicating if it in a sphere (3	bus flux (φuse), refers to the flux 360º), in a wide in a narrow cone	1 400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode expressed in W	power (P _{on}), /	14,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P _{net}) essed in W and e second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer dimensions without	Height	912	Spectral power	See image		
	Width	26	distribution in the	in last page		
	Depth	26		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	94			
		Chromaticity coordinates (x and y)	0,379 0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-20	Survival factor	0,95			
the lumen maintenance factor	0,80					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	1			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-' : not applicable;

(b)'_-' : not applicable;

Spectrum

