Product Information Sheet

sions without

separate con-

trol gear, light-

control

ing

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	, , ,		0, 0
Supplier's name or trade mark:	LUMIT		
Supplier's address: INTERLUSA,	Estr. interior da ciro	cunvalação 12477, 4100-	-178 Porto, PT
Model identifier: A065805l1B			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	N/A		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	No
	Product para	meters	
Parameter	Value	Parameter	Value
	General product	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	5	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	450 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), ex- pressed in W	5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	-
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen- Height	35	Spectral power dis-	See image

22

300

tribution in the

range 250 nm to 800

nm, at full-load

in last page

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,386 0,390		
Parameters for LED and OLED light sources:					
R9 colour rendering index valu	e -26	Survival factor	1,00		
the lumen maintenance factor	-				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,80	Colour consistency in McAdam ellipses	2		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	t	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	-		

(a)'-': not applicable; (b)'-': not applicable;

