## **Product Information Sheet**

ing

control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

| COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources                                      |              |                                 |  |              |  |  |  |
|--|--------------|---------------------------------|--|--------------|--|--|--|
| Supplier's name or trade mark: LUMIT   |              |                                 |  |              |  |  |  |
| Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT   |              |                                 |  |              |  |  |  |
| Model identifier: A06581601B   |              |                                 |  |              |  |  |  |
| Type of light so   | urce:        |                                 |  |              |  |  |  |
| Lighting technology used:  |              | LED                             | Non-directional or directional:  | NDLS         |  |  |  |
| Light source cap   | -type        | N/A                             |  |              |  |  |  |
| (or other electri  | c interface) |                                 |  |              |  |  |  |
| Mains or non-mains:  |              | MLS                             | Connected light source (CLS):  | No           |  |  |  |
| Colour-tuneable light source:  |              | No                              | Envelope:  | -            |  |  |  |
| High luminance light source:   |              | No                              |  |              |  |  |  |
| Anti-glare shield:   |              | Yes                             | Dimmable:  | No           |  |  |  |
| Product parameters   |              |                                 |  |              |  |  |  |
| Parameter  |              | Value                           | Parameter  | Value        |  |  |  |
| General product parameters:  |              |                                 |  |              |  |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |              | 16                              | Energy efficiency class  | F            |  |  |  |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |              | 1 440 in Nar-<br>row cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000        |  |  |  |
| On-mode power (P <sub>on</sub> ), expressed in W   |              | 16,0                            | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | -            |  |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |              | -                               | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |  |  |  |
| Outer dimen-   | Height       | 35                              | Spectral power dis-  | See image    |  |  |  |
| sions without  | Width        | 22                              | tribution in the   | in last page |  |  |  |
| separate con-<br>trol gear, light-   | Depth        | 1 174                           | range 250 nm to 800<br>nm, at full-load  |              |  |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre)  |  |      |  |                |  |  |  |
|---|--|------|--|----------------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>  |  | -    | If yes, equivalent power (W)           | -              |  |  |  |
|   |  |      | Chromaticity coordinates (x and y)     | 0,368<br>0,374 |  |  |  |
| Parameters for LED and OLED light sources:  |  |      |  |                |  |  |  |
| R9 colour rendering index value   |  | 16   | Survival factor                        | 1,00           |  |  |  |
| the lumen maintenance factor  |  | -    |  |                |  |  |  |
| Parameters for LED and OLED mains light sources:  |  |      |  |                |  |  |  |
| displacement factor (cos φ1)  |  | 0,80 | Colour consistency in McAdam ellipses  | 2              |  |  |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. |  | _(b) | If yes then replace-<br>ment claim (W) | -              |  |  |  |
| Flicker metric (Pst LM)   |  | 0,1  | Stroboscopic effect metric (SVM)       | -              |  |  |  |

(a)'-': not applicable; (b)'-': not applicable;

