## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: LUMIT

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

## Model identifier: A1098X501B

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Parameter		Value	Parameter	Value			
General product parameters:							
Energy consum mode (kWh/10 up to the neares	00 h), rounded	5	Energy efficiency class	F			
Useful luminous dicating if it refe a sphere (360°), (120°) or in a na	ers to the flux in in a wide cone	530 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	4 000			
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	5,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	-			
Networked st (P <sub>net</sub> ) for CLS, e and rounded to imal	•	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimen-	Height	90	Spectral power dis-	See image			
sions without separate con- trol gear, light- ing control	Width Depth	90 50	tribution in the range 250 nm to 800 nm, at full-load	in last page			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi- nates (x and y)	0,314 0,335			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	3	Survival factor	1,00			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,5	Stroboscopic effect metric (SVM)	0,3			

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

