Product Information Sheet

without

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLLGAILD KLGOI	LATION (LO) 2013/2	ora with regard to energ	gy labelling of light			
Supplier's name	or trade mark:	LED EVOLUTION					
Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT							
Model identifie	r: E14-E-5W-S						
Type of light so	urce:						
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap	o-type	E14					
(or other electri	c interface)						
Mains or non-mains:		MLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance light source:		No					
Anti-glare shield:		No	Dimmable:	No			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	G			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 400			
On-mode power (P _{on}), expressed in W		5,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			
Outer dimensions	Height	82	Spectral power	See image			
uimensions	Width	45	distribution in the	in last page			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)		Yes	If yes, equivalent power (W)	35			
			Chromaticity	0,437			
			coordinates (x and y)	0,402			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		2	Survival factor	0,95			
the lumen maintenance factor		0,80					
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)		0,40	Colour consistency in McAdam ellipses	2			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	0,4			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

