Product Information Sheet

without

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLLOAILD KLOOI	LATION (LO) 2013/2	ora with regard to energ	gy labelling of light		
Supplier's name	e or trade mark:	LED EVOLUTION				
Supplier's addre	ess: INTERLUSA,	Estr. interior da circ	unvalação 12477, 4100-	178 Porto, PT		
Model identifie	r: E14-V-5W-B					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap	o-type	E14				
(or other electri	ic interface)					
Mains or non-mains:		MLS	Connected light source (CLS):	No		
Colour-tuneable	Colour-tuneable light source:		Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	G		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P _{on}), expressed in W		5,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer dimensions	Height Width	100 37	Spectral power distribution in the	See image in last page		
1						

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	35			
		Chromaticity	0,438			
		coordinates (x and y)	0,408			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,95			
the lumen maintenance factor	0,80					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,40	Colour consistency in McAdam ellipses	3			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

Spectrum

